

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- AC INLET: AC cable attached
- Power: 12-24W series
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 68.5*50*26.5mm(exclude plug)
- Application: Consumer electronics, Telecom and office equipment



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55035 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

12W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-00050200-S10	100-240VAC	10W	5V	2.0A	C6,C8 or AC cable attached
SW-00050240-S10	100-240VAC	12W	5V	2.4A	C6,C8 or AC cable attached
SW-00090100-S10	100-240VAC	9W	9V	1.0A	C6,C8 or AC cable attached
SW-00120100-S10	100-240VAC	12W	12V	1.0A	C6,C8 or AC cable attached
SW-00150080-S10	100-240VAC	12W	15V	0.8A	C6,C8 or AC cable attached
SW-00240050-S10	100-240VAC	12W	24V	0.5A	C6,C8 or AC cable attached

24W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-00050400-S10	100-240VAC	20W	5V	4.0A	C6,C8 or AC cable attached
SW-00090250-S10	100-240VAC	22.5W	9V	2.5A	C6,C8 or AC cable attached
SW-00120200-S10	100-240VAC	24W	12V	2.0A	C6,C8 or AC cable attached
SW-00150160-S10	100-240VAC	24W	15V	1.6A	C6,C8 or AC cable attached
SW-00240100-S10	100-240VAC	24W	24V	1.0A	C6,C8 or AC cable attached

Mechanical Diagram:

