



FEATURES:

- Input: AC 100-240V~ 50/60Hz
- AC INLET: C8 or C6 or C14
- Power: 48-65W series
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 111*51.5*33.5mm(exclude plug)
- Application: Consumer electronics, Teleco and office equipment



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55035 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

48W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-00090500-S10	100-240VAC	45W	9V	5.0A	C8, C6, C14
SW-00120400-S10	100-240VAC	48W	12V	4.0A	C8, C6, C14
SW-00150300-S10	100-240VAC	45W	15V	3.0A	C8, C6, C14
SW-00240200-S10	100-240VAC	48W	24V	2.0A	C8, C6, C14
SW-00480100-S10	100-240VAC	48W	48V	1.0A	C8, C6, C14

60W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-00090600-S10	100-240VAC	54W	9V	6.0A	C8, C6, C14
SW-00120500-S10	100-240VAC	60W	12V	5.0A	C8, C6, C14
SW-00150400-S10	100-240VAC	60W	15V	4.0A	C8, C6, C14
SW-00240250-S10	100-240VAC	60W	24V	2.5A	C8, C6, C14
SW-00480125-S10	100-240VAC	60W	48V	1.25A	C8, C6, C14

Mechanical Diagram:

