

### FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: US, CN plug
- Power: 5V 2.4A DUAL OUTPUT
- Ovp, Ocp, Scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 41.6\*32.4\*27.5mm(exclude plug)
- Application: Tablet, Mobile phone, etc...



### SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

### MODEL NO: DK46T

MODEL	INPUT VOLTAGE	POWER	OUTPUT	OUTPUT CURRENT	PLUG TYPE
DK46T	100-240VAC	12W	PORT 1	5V 2.4A	US/CN PLUG
			PORT 2	5V 2.4A	

### Mechanical Diagram

