

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: US, EU plug
- Power: TYPE C + TYPE C total 48W PD
- Ovp, Ocp, Scp and Over load protection
- GAN TECH, PD Charger, smart
- Efficiency level: VI
- Dimension: 52.4*42.8*32.1mm(exclude plug)
- Application: Tablet, Mobile phone, etc...



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2, -3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
QC60S	USB C PORT 1	PD: 5V3, 9V2.22A, 12V1.65A, 20V1.5A	30W	38W
	USB A PORT 2	QC: 5V3, 9V2A, 12V1.5A	18W	
MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
QC32	USB C PORT 1	PD: 5V3, 9V3A, 20V1.75A	35W	35W
	USB C PORT 2	PD: 5V3, 9V3A, 20V1.75A	35W	
MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
QC23	USB C PORT 1	PD: 5V3, 9V3A, 15V3A, 20V2.25A	45W	45W
	USB C PORT 2	PD: 5V3, 9V3A, 15V3A, 20V2.25A	45W	

Mechanical Diagram:

