

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: US, EU plug
- Power: TYPE C + USB A total 18W PD
- Ovp, Ocp, Scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 45.8*30*35.8mm(exclude plug)
- Application: Tablet, Mobile phone, etc...



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2, -3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

MODEL	USB PORT	OUTPUT	POWER	AC PLUG
QC51	USB C port	PD: 5V3, 9V2A, 12V1.5A	18W	US/EU/UK plug
	USB A PORT 1	QC: 5V3, 9V2A, 12V1.5A	18W	

Mechanical Diagram:

