

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: C8 inlet
- Port: 4xTYPE C port
- Ovp, Ocp, Scp and Over load protection
- GAN TECH, 200W PD Charger, smart
- Efficiency level: VI
- Dimension: 100.0\*72.0\*32.0mm(exclude plug)
- Protocol: TypeC PD2.0/PD3.0/PD3.1/PPS, QC4/QC4+/QC3.0/QC2.0 , FCP, SCP, AFC, Apple2.4 , BC1.2, MTK



SAFETY:

| SAFETY:         |                                                                                                                                                                                   |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Safety Standard | UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065                                                                                                                       |
| Safety Approval | UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV                                                                                                                                      |
| EMC Standard    | EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2, -3, EAC TP TC 020<br>EMC IMMUNITY: EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024; light industry level, criteria A, EAC TP TC 020 |
| MTBF            | 50K hrs min. MIL-HDBK-217F (25°C)                                                                                                                                                 |

MODEL LIST:

| MODEL          | USB PORT     | OUTPUT                              | Single Port POWER | TOTAL POWER |
|----------------|--------------|-------------------------------------|-------------------|-------------|
| MU4200D-GaN 4C | USB C PORT 1 | PD: 5V3A, 9V3A, 12V3A, 15V3A, 20V5A | 100W              | 140W        |
|                | USB C PORT 2 | PD: 5V3A, 9V3A, 12V3A, 15V3A, 20V5A | 100W              |             |
|                | USB C PORT 3 | PD: 5V3A, 9V3A, 12V3A, 15V3A, 20V5A | 100W              |             |
|                | USB C PORT 4 | PD: 5V3A, 9V3A, 12V3A, 15V3A, 20V5A | 100W              |             |

Mechanical Diagram:

