

### FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: US, EU plug
- Power: 12W DUAL USB
- Ovp, Ocp, Scp and Over load protection
- Ripple < 100mV
- Efficiency level: VI
- Dimension: 52.4\*42.8\*32.1mm(exclude plug)
- Application: Tablet, Mobile phone, etc...



### SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2, -3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

### MODEL LIST:

MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
DK15T	USBA PORT 1	5V 2.4A	12W	12W
	USBA PORT 2	5V 2.4A	12W	

### Mechanical Diagram:

